



---

How to Use



# How to USE

## **Yacht Washing**

**Dilution Rate :** *Dirty Surface* : 100 ml in to 10 lt. water / *Grasy and Dirty Surface* : 150 ml in to 10 lt. water

**Equipments :** Brush / Sponge

Read *CAUTIONS* good. Put 100 ml in a bucket of 10 lt. water. Apply the solution with a sponge or soft brush on the surface. Rinse with fresh water.

## **Teak Cleaning**

**Dilution Rate :** *Dirty Surface* : 1:1 / *Grasy and Dirty Surface* : Pure

**Equipments :** Deck Brush / Scrub Pad

Read *CAUTIONS* good. Wet the teak surface and then depending on the degree of contamination, apply the product directly or dilute 1:1 to surface and allow it to remain on the stained areas 1-2 minutes. Scrub with the scrub pad before rinsing well with fresh water.

**Hydraulic Fluid Stains :** If hydraulic fluid has spilled on your teak and has remained there for a long time and has penetrated into it, you can try this product instead of replacing the teak deck.

Wet the stained area with hot water. Apply the product directly and allow it to remain on the stained area for 3-4 hours. Then wet the surface again with fresh water and scrub with a scub pad. Rinse with fresh water and allow the surface to dry. Once the surface is dry, most of the stain will be gone. If you still see stain, repeat this cycle one more time.

## **Inflatable & RIB Boat Cleaning / Fender Cleaning**

**Dilution Rate :** Pure

**Equipments :** Sponge / Microfiber Clothes

Read *CAUTIONS* good. Wet the surface and apply the product directly and allow it to remain on the ined areas 1-2 minutes. Scrub with sponge or wipe with wet microfiber cloths before rinsing well with fresh water.

# Wash & Wax

# How to USE

## Yacht Washing

**Dilution Rate :** 100 ml in to 10 lt water

**Equipments :** Brush / Sponge

Put 100 ml. in a bucket of 10 lt. water. Apply with a sponge or soft brush on the surface. Don't let it dry. Rinse with fresh water.



# How to USE

## **Teak Cleaning & Brightening**

**Dilution Rate :** Pure

**Equipments :** Deck Brush / Scrub Pad

Read *CAUTIONS* good. Wet the teak surface and remove dust for better product penetration. After water has drained from the surface spread out product on the moist surface ( 1 lt. to 10 m<sup>2</sup> ), ensuring the entire surface is evenly covered and saturated. Allow it to remain 3-5 minutes on the stained area. Scrub with the scrub pad before rinsing well with fresh water. Do not let the product dry on the surface, if it dries, wet the surface again and continue scrubbing.

If your teak deck very old, grey and there are white hairs like velvet on the surface it can also be applied to dry surfaces. Put the product in a bucket and spread it on the surface with a brush. Allow it to remain 2-3 minutes on the stained area. Then wet the surface and scrub with the scrub pad before rinsing well with fresh water. Do not let the product dry on the surface, if it dries, wet the surface again and continue scrubbing.

# **Black Stain REMOVER**

# How to USE

## **Exhaust (soot) / Black Streaks Cleaning**

**Dilution Rate :** Pure

**Equipments :** Sponge / Microfiber Cloth / Soft Scrub Pad

Read *CAUTIONS* good. Turn the nozzle to the 'SPRAY' or 'STREAM' position then apply directly to surface, depending on the degree of contamination allow the product to remain on the stained areas 20 sec- 1 min. Then wipe with wet microfiber cloth / sponge or scrub with soft scrub pad before rinsing well with water.

# Rust Stain REMOVER

# How to USE

## **Rust Stains / Calcium ( Lime ) Stains Cleaning**

**Dilution Rate :** Pure

**Equipments :** Sponge / Microfiber Cloth / Soft Scrub Pad

Read *CAUTIONS* good. Turn the nozzle to the 'SPRAY' or 'STREAM' position then apply directly to surface, depending on the degree of contamination allow the product to remain on the stained areas 30 sec.-2 min. Then wipe with wet microfiber cloth / sponge or scrub with soft scrub pad before rinsing well with water.

## **Hull Cleaning ( Yellow Stains )**

**Dilution Rate :** Pure

**Equipments :** Sponge / Microfiber Cloth / Soft Scrub Pad

Read *CAUTIONS* good. Turn the nozzle to the 'SPRAY' or 'STREAM' position then apply product to surface, allow the product to remain on the stained area until the surface is well whitened then rinse well with water. Deep stains may require a second application and light scrubbing.

# Teak Spray

# How to USE

## **Removing Stains on Teak Deck Quikly**

**Equipments** : Brush

Read *CAUTIONS* good. Shake bottle well before use. Spray spot remover evenly on the stain directly from the bottle. Leave it on the stained area for 5-10 minutes. Scrub with a gentle brush till the stain has been dissolved. Repeat this cycle again if necessary.

Before using OCTO Teak Spray it is advisable to make a small test at a non-visible place of the floor to ensure there will be no undesired reaction.

# Contact Us

[www.octobiomarine.com](http://www.octobiomarine.com)

[\*\*info@octobiomarine.com\*\*](mailto:info@octobiomarine.com)



+90 545 9101978

+90 533 3446444